

Modell PN 6/10/16 190 °C	Teller	DN	Luftschleuse	passend zwischen flachdichtende Verschraubungen	≈ mm	Bestellnummer
PF-	Teflon	20		G 1 ¼" = DN 32	38	PF -T 2032
PF-	Teflon	20	L	G 1 ¼" = DN 32	38	PF -TL 2032
PF-	Teflon	20		G 1" = DN 25	30	PF -T 2025
PF-	Teflon	20	L	G 1" = DN 25	30	PF -TL 2025
PF-	Teflon	20		G ¾" = DN 20	24	PF -T 2020
PF-	Teflon	20	L	G ¾" = DN 20	24	PF -TL 2020
PF-	Teflon	25		G 1 ½" = DN 40	44	PF -T 2540
PF-	Teflon	25	L	G 1 ½" = DN 40	44	PF -TL 2540
PF-	Teflon	25		G 1 ¼" = DN 32	38	PF -T 2532
PF-	Teflon	25	L	G 1 ¼" = DN 32	38	PF -TL 2532
PF-	Teflon	25		G 1" = DN 25	30	PF -T 2525
PF-	Teflon	25	L	G 1" = DN 25	30	PF -TL 2525
PF-	Teflon	32		G 2" = DN 50	55	PF -T 3250
PF-	Teflon	32	L	G 2" = DN 50	55	PF -TL 3250
PF-	Teflon	32		G 1 ½" = DN 40	44	PF -T 3240
PF-	Teflon	32	L	G 1 ½" = DN 40	44	PF -TL 3240
PF-	Teflon	32		G 1 ¼" = DN 32	38	PF -T3232
PF-	Teflon	32	L	G 1 ¼" = DN 32	38	PF -TL3232
PF-	Teflon	40		60mm	60	PF -T40_60
PF-	Teflon	40	L	60mm	60	PF -TL40_60
PF-	Teflon	40		70mm	71	PF -T40_70
PF-	Teflon	40	L	70mm	71	PF -T40_70



SPEZIALARMATUREN®